




## PRODUCT FACT SHEET

### Strion™ High Performance Rechargeable Xenon Flashlight

MARKET APPLICATIONS:	Premium Professional Light - Industrial, Law Enforcement, Outdoor
DESCRIPTION:	An ultra-compact, high performance rechargeable xenon flashlight
CASE MATERIAL:	Machined Aircraft Aluminum with anodized finish
DIMENSIONS:	Length: 5.3 in. (13.46 cm)      Head diameter: 1.25 in. (3.18 cm) Barrel diameter: 0.945 in. (2.40 cm)
WEIGHT:	With battery - 0.29 lbs. (8.22 grams)
LENS:	Borofloat High Temperature Glass
LIGHT SOURCE:	3.6 Volt, 6.12 Watt, 1.7A (type T-1½ ), xenon gas-filled, Bi-Pin bulb; spare lamp in the tailcap
LIGHT OUTPUT:	Up to 12,000 Peak Beam Candlepower, Bulb Rating: 116 Lumens Typical
ON/OFF:	Pushbutton tailcap - momentary; Rotate tailcap - Constant on.
RUN TIME:	70 minutes continuous use between charges
BATTERY:	Lithium Ion with on-board safety control circuit, 3.75 Volts, 2000 mAh minimum (WT = .11 lbs.), rechargeable up to 300 times
CHARGING:	Clamp style charge holder with digital control circuit that prevents overcharge; Rapid charge time is 2.5 hours Charges battery in product: LED Steady - Charging; LED Blinking - Charged
FEATURES:	Adjustable Focus, Water Resistant, O Ring Sealed, Serialized for Identification.
APPROVALS:	
WARRANTY:	"No Excuses" limited lifetime warranty.
OPTIONAL ACCESSORIES:	Colored filters, holster, Traffic Wand

Assembled In The USA.

Document #145

Issued: 10/01/04  
Revised: Rev:

Page 1 of 1