



PRODUCT FACT SHEET

STREAMLIGHT ULTRASTINGER® RECHARGEABLE FLASHLIGHT

MARKET APPLICATIONS:	Law enforcement, sporting goods, security, fire & rescue, hardware/tool, automotive, industrial, consumer.
DESCRIPTION:	The UltraStinger is a high-intensity, extremely bright rechargeable flashlight featuring a beam of up to 75,000 peak beam candlepower and up to one hour of continuous run time.
CASE MATERIAL:	Machined aircraft aluminum that is anodized against corrosion inside and out.
DIMENSIONS:	Length: 11.75 in. (30 cm) Diameter: Major Diameter: 2.37 in. (6.02 cm) Body Diameter: 1.08 in. (2.74 cm)
WEIGHT:	16.1 oz (500 grams)*
LENS:	Unbreakable polycarbonate lens with scratch resistant coating.
LIGHT SOURCE:	30 hour life xenon halogen gas-filled bi-pin bulb. Variable spot to flood beam
LIGHT OUTPUT:	Up to 75,000 Peak beam candlepower. Bulb Rating: 295 Lumens Typical
ON/OFF:	Push-button head switch. Momentary or constant on.
RUN TIME:	Up to one hour of continuous use.
BATTERY:	6 volt nickel-cadmium 5 cell sub-C battery is rechargeable up to 1,000 times
CHARGING:	Ten hours to fully recharge on 100V, 120V, 230V or 240V AC, or 12V DC. 2.5 hour fast charger also available.**
FEATURES:	LED charge-continuity indicator. Compact, snap-in charger that mounts in any Position, Serialized for positive identification.
APPROVALS:	Most models meet applicable European Community Directives. CE
WARRANTY:	"No Excuses" limited lifetime warranty.
OPTIONAL ACCESSORIES:	Ring holder, safety wands, 5-unit bank charger, 2.5 hour fast charger and 120 Volt Fast Charge Cord**

* With battery (included in purchase)

** 120 Volt AC Fast Charge Cord P/N 22665, or DC P/N 22051 vehicle cord required to Fast Charge an UltraStinger

Assembled In The USA.

Document #103

Issued: 10/01/04
Revised: Rev:

Page 1 of 1